K/YSUN J

Dimension and Wall Thickness to ANSI B36.19/B36.10

						_			_	_	_		_	_		_	_		
NPS	OD(mm)	sch5s	sch10s	sch10	sch20	sch30	sch40s	STD	sch40	sch60	sch80s	XS	sch80	sch100	sch120	sch140	sch160	XXS	
1/8	10.3		1.24				1.73	1.73	1.73		2.41	2.41	2.41						
1/4	13.7		1.65				2.24	2.24	2.24		3.02	3.02	3.02						
3/8	17.1		1.65				2.31	2.31	2.31		3.2	3.2	3.2						
1/2	21.3	1.65	2.11				2.77	2.77	2.77		3.73	3.73	3.73				4.78	7.47	
3/4	26.7	1.65	2.11				2.87	2.87	2.87		3.91	3.91	3.91				5.56	7.82	
1	33.4	1.65	2.77				3.38	3.38	3.38		4.55	4.55	4.55				6.35	9.09	
1 1/4	42.2	1.65	2.77				3.56	3.56	3.56		4.85	4.85	4.85				6.35	9.7	
1 1/2	48.3	1.65	2.77				3.68	3.68	3.68		5.08	5.08	5.08				7.14	10.15	
2	60.3	1.65	2.77				3.91	3.91	3.91		5.54	5.54	5.54				8.74	11.07	
2 1/2	73	2.11	3.05				5.16	5.16	5.16		7.01	7.01	7.01				9.53	14.02	
3	88.9	2.11	3.05				5.49	5.49	5.49		7.62	7.62	7.62				11.13	15.24	
3 1/2	101.6	2.11	3.05				5.74	5.74	5.74		8.08	8.08	8.08						
4	114.3	2.11	3.05				6.02	6.02	6.02		8.56	8.56	8.56		11.13		13.49	17.12	
5	141.3	2.77	3.4				6.55	6.55	6.55		9.53	9.53	9.53		12.7		15.88	19.05	
6	168.3	2.77	3.4				7.11	7.11	7.11		10.97	10.97	10.97		14.27		18.26	21.95	
8	219.1	2.77	3.76		6.35	7.04	8.18	8.18	8.18	10.31	12.7	12.7	12.7	15.09	18.26	20.62	23.01	22.23	
10	273.1	3.4	4.19		6.35	7.8	9.27	9.27	9.27	12.7	12.7	12.7	15.09	18.26	21.44	25.4	28.58	25.4	
12	323.9	3.96	4.57		6.35	8.38	9.53	9.53	10.31	14.27	12.7	12.7	17.48	21.44	25.4	28.58	33.32	25.4	
14	355.6	3.96	4.78	6.35	7.92	9.53		9.53	11.13	15.09		12.7	19.05	23.83	27.79	31.75	35.71		
16	406.4	4.19	4.78	6.35	7.92	9.53		9.53	12.7	16.66		12.7	21.44	26.19	30.96	36.53	40.49		
18	457.2	4.19	4.78	6.35	7.92	11.13		9.53	14.27	19.05		12.7	23.83	29.36	34.93	39.67	45.24		
20	508	4.78	5.54	6.35	9.53	12.7		9.53	15.09	20.62		12.7	26.19	32.54	38.1	44.45	50.01		
22	558.8	4.78	5.54	6.35	9.53	12.7		9.53		22.23		12.7	28.58	34.93	41.28	47.63	53.98		
24	609.6	5.54	6.35	6.35	9.53	14.27		9.53	17.48	24.61		12.7	30.96	38.89	46.02	52.37	59.54		
26	660.4			7.92	12.7			9.53				12.7	Comments: SCH5S,10S,40S,80S are used for Stainless Steel Pipes and Fittings ASME/ANSI B36.19/B36.10						
28	711.2			7.92	12.7	15.88		9.53				12.7							
30	762	6.35	7.92	7.92	12.7	15.88		9.53				12.7							
32	812.8			7.92	12.7	15.88	17.48	9.53	17.48			12.7							
34	863.6			7.92	12.7	15.88	17.48	9.53	17.48			12.7							
36	914.4			7.92	12.7	15.88	19.05	9.53	19.05			12.7							
38	965.2							9.53				12.7							
40	1016							9.53				12.7							
42	1066.8							9.53				12.7							
44	1117.6							9.53				12.7							
46	1168.4							9.53				12.7							
48	1219.2							9.53				12.7							